


Inner bore d ₁ mm	Bearing number	Principal dimensions					Lock nut	Locking device	Appropriate hydraulic nut	Weight kg(s).
		d	d ₃	B ₁ mm	B ₂	G				
20	H 205	25	38	26	8.0	M 25 X 1.5	KM 5	MB 5	-	0.064
25	H 206	30	45	27	8.0	M 30 X 1.5	KM 6	MB 6	-	0.086
30	H 207	35	52	29	9.0	M 35 X 1.5	KM 7	MB 7	-	0.120
35	H 208	40	58	31	10.0	M 40 X 1.5	KM 8	MB 8	-	0.160
40	H 209	45	65	33	11.0	M 45 X 1.5	KM 9	MB 9	-	0.210
45	H 210	50	70	35	12.0	M 50 X 1.5	KM 10	MB 10	HMV 10	0.240
50	H 211	55	75	37	12.5	M 55 X 2.0	KM 11	MB 11	HMV 11	0.280
55	H 212	60	80	38	13.0	M 60 X 2.0	KM 12	MB 12	HMV 12	0.310
60	H 213	65	85	40	14.0	M 65 X 2.0	KM 13	MB 13	HMV 13	0.360
65	H 215	75	98	43	15.0	M 75 X 2.0	KM 15	MB 15	HMV 15	0.660
70	H 216	80	105	46	17.0	M 80 X 2.0	KM 16	MB 16	HMV 16	0.810
75	H 217	85	110	50	18.0	M 85 X 2.0	KM 17	MB 17	HMV 17	0.940
80	H 218	90	120	52	18.0	M 90 X 2.0	KM 18	MB 18	HMV 18	1.100
100	H 222	110	145	63	21.0	M 110X2.0	KM 22	MB 22	HMV 22	1.800

Technical supplement


Cages	Precision	Grease
Steel - <input checked="" type="checkbox"/>	Normal (ISO)	Nil
Polymid - <input checked="" type="checkbox"/>		
Brass - <input checked="" type="checkbox"/>		



Inner bore d ₁ mm	Bearing number	Principal dimensions					Lock nut	Locking device	Appropriate hydraulic nut	Weight kg(s).
		d	d ₃	B ₁ mm	B ₂	G				
20	H 305	25	38	29	8.0	M 25 X 1.5	KM 5	MB 5	-	0.071
25	H 306	30	45	31	8.0	M 30 X 1.5	KM 6	MB 6	-	0.095
30	H 307	35	52	35	9.0	M 35 X 1.5	KM 7	MB 7	-	0.140
35	H 308	40	58	36	10.0	M 40 X 1.5	KM 8	MB 8	-	0.170
40	H 309	45	65	39	11.0	M 45 X 1.5	KM 9	MB 9	-	0.230
45	H 310	50	70	42	12.0	M 50 X 1.5	KM 10	MB 10	HMV 10	0.270
50	H 311	55	75	45	12.5	M 55 X 2.0	KM 11	MB 11	HMV 11	0.320
55	H 312	60	80	47	13.0	M 60 X 2.0	KM 12	MB 12	HMV 12	0.360
60	H 313	65	85	50	14.0	M 65 X 2.0	KM 13	MB 13	HMV 13	0.420
65	H 315	75	98	55	15.0	M 75 X 2.0	KM 15	MB 15	HMV 15	0.780
70	H 316	80	105	59	17.0	M 80 X 2.0	KM 16	MB 16	HMV 16	0.950
75	H 317	85	110	63	18.0	M 85 X 2.0	KM 17	MB 17	HMV 17	1.100
80	H 318	90	120	65	18.0	M 90 X 2.0	KM 18	MB 18	HMV 18	1.300
85	H 319	95	125	68	19.0	M 95 X 2.0	KM 19	MB 19	HMV 19	1.400
90	H 320	100	130	71	20.0	M 100X2.0	KM 20	MB 20	HMV 20	1.600
100	H 322	110	145	77	21.0	M 110X2.0	KM 22	MB 22	HMV 22	2.050

Technical supplement


Cages	Precision	Grease
Steel - <input checked="" type="checkbox"/>	Normal (ISO)	Nil
Polymid - <input checked="" type="checkbox"/>		
Brass - <input checked="" type="checkbox"/>		




Inner bore d ₁ mm	Bearing number	Principal dimensions					Lock nut	Locking device	Appropriate hydraulic nut	Weight kg(s).
		d	d ₃	B ₁ mm	B ₂	G				
20	H 2305	25	38	35	8.0	M 25 X 1.5	KM 5	MB 5	-	0.085
25	H 2306	30	45	38	8.0	M 30 X 1.5	KM 6	MB 6	-	0.110
30	H 2307	35	52	43	9.0	M 35 X 1.5	KM 7	MB 7	-	0.165
35	H 2308	40	58	46	10.0	M 40 X 1.5	KM 8	MB 8	-	0.224
40	H 2309	45	65	50	11.0	M 45 X 1.5	KM 9	MB 9	-	0.270
45	H 2310	50	70	55	12.0	M 50 X 1.5	KM 10	MB 10	HMV 10	0.340
50	H 2311	55	75	59	12.5	M 55 X 2.0	KM 11	MB 11	HMV 11	0.390
55	H 2312	60	80	62	13.0	M 60 X 2.0	KM 12	MB 12	HMV 12	0.450
60	H 2313	65	85	65	14.0	M 65 X 2.0	KM 13	MB 13	HMV 13	0.520
65	H 2315	75	98	73	15.0	M 75 X 2.0	KM 15	MB 15	HMV 15	1.100
70	H 2316	80	105	78	17.0	M 80 X 2.0	KM 16	MB 16	HMV 16	1.280
75	H 2317	85	110	82	18.0	M 85 X 2.0	KM 17	MB 17	HMV 17	1.350
80	H 2318	90	120	86	18.0	M 90 X 2.0	KM 18	MB 18	HMV 18	1.600
85	H 2319	95	125	90	19.0	M 95 X 2.0	KM 19	MB 19	HMV 19	1.800
90	H 2320	100	130	97	19.0	M 100X2.0	KM 20	MB 20	HMV 20	2.000
100	H 2322	110	145	105	21.0	M 110X2.0	KM 22	MB 22	HMV 22	2.750
110	H 2324	120	155	112	22.0	M 120X2.0	KM 24	MB 24	HMV 24	3.000
115	H 2326	130	165	121	23.0	M 130X2.0	KM 26	MB 26	HMV 26	4.450
125	H 2328	140	180	131	24.0	M 140X2.0	KM 28	MB 28	HMV 28	5.400
135	H 2330	150	195	139	26.0	M 150X2.0	KM 30	MB 30	HMV 30	6.400
140	H 2332	160	210	147	28.0	M 160X3.0	KM 32	MB 32	HMV 32	8.800

Technical supplement

Cages	Precision	Grease
Steel - <input checked="" type="checkbox"/>	Normal (ISO)	Nil
Polymid - <input checked="" type="checkbox"/>		
Brass - <input checked="" type="checkbox"/>		



Inner bore d ₁ mm	Bearing number	Principal dimensions					Lock nut	Locking device	Appropriate hydraulic nut	Weight kgs.
		d	d ₃	B ₁ mm	B ₂	G				
110	H 3124	120	155	88	22	M 120 X 2	KM 24	MB 24	HMV 24	2.50
115	H 3126	130	165	92	23	M 130 X 2	KM 26	MB 26	HMV 26	3.45
125	H 3128	140	180	97	24	M 140 X 2	KM 28	MB 28	HMV 28	4.10
135	H 3130	150	195	111	26	M 150 X 2	KM 30	MB 30	HMV 30	5.25
140	H 3132	160	210	119	28	M 160 X 3	KM 32	MB 32	HMV 32	7.25



Technical supplement

Cages	Precision	Grease
Steel - <input checked="" type="checkbox"/>	Normal (ISO)	Nil
Polymid - <input checked="" type="checkbox"/>		
Brass - <input checked="" type="checkbox"/>		