



Shaft dia. mm inch	Unit number	Nominal dimensions										Bolt size mm inch	Bearing number	Housing number	Mass of unit Kg
		h	a	e	b	s ₁	s ₂	g	w	Bi	n				
12 1/2	UCPA 201	30.2	76	52	40	11	62	13	M 10	31.0	12.7	M 10	UC 201	PA 204	0.57
	UCPA 201-8	1-3/16	2-63/64	2-1/16	1-37/64	7/16	2-7/16	3/64	3/8	1.2205	0.5000	3/8	UC 201-8		0.57
15 5/8	UCPA 202	30.2	76	52	40	11	62	13	M 10	31.0	12.7	M 10	UC 202	PA 204	0.56
	UCPA 202-10	1-3/16	2-63/64	2-1/16	1-37/64	7/16	2-7/16	3/64	3/8	1.2205	0.5000	3/8	UC 202-10		0.56
17 11/16	UCPA 203	30.2	76	52	40	11	62	13	M 10	31.0	12.7	M 10	UC 203	PA 204	0.55
	UCPA 203-11	1-3/16	2-63/64	2-1/16	1-37/64	7/16	2-7/16	3/64	3/8	1.2205	0.5000	3/8	UC 203-11		0.55
20 3/4	UCPA 204	30.2	76	52	40	11	62	13	M 10	31.0	12.7	M 10	UC 204	PA 204	0.53
	UCPA 204-12	1-3/16	2-63/64	2-1/16	1-37/64	7/16	2-7/16	3/64	3/8	1.2205	0.5000	3/8	UC 204-12		0.54
25 1	UCPA 205	36.5	84	56	38	12	72	15	M 10	34.1	14.3	M 10	UC 205	PA 205	0.71
	UCPA 205-16	1-7/16	3-5/16	2-13/64	1-1/2	15/32	2-53/64	19/32	3/8	1.3425	0.5630	3/8	UC 205-16		0.70
30 1-1/8 1-1/4	UCPA 206	42.9	94	66	48	13	84	18	M 14	38.1	15.9	M 14	UC 206	PA 206	1.07
	UCPA 206-18	1-11/16	3-45/64	2-19/32	1-57/64	3/64	3-5/16	45/64	1/2	1.5000	0.6260	1/2	UC 206-18		1.09
	UCPA 206-20												UC 206-20		1.05
35 1-1/4 1-3/8	UCPA 207	47.6	110	80	48	13	95	20	M 14	42.9	17.5	M 14	UC 207	PA 207	1.49
	UCPA 207-20	1-7/8	4-21/64	3-5/32	1-57/64	3/64	3-47/64	25/32	1/2	1.6890	0.6890	1/2	UC 207-20		1.55
	UCPA 207-22												UC 207-22		1.50
40 1-1/2	UCPA 208	49.2	116	84	54	13	100	20	M 14	49.2	19.0	M 14	UC 208	PA 208	1.75
	UCPA 208-24	1-15/16	4-9/16	3-5/16	2-1/8	3/64	3-15/16	25/32	1/2	1.9370	0.7480	1/2	UC 208-24		1.79
45 1-5/8 1-3/4	UCPA 209	54.2	120	90	60	13	108	25	M 14	49.2	19.0	M 14	UC 209	PA 209	2.17
	UCPA 209-26	2-9/64	4-23/32	3-35/64	2-23/64	3/64	4-1/4	63/64	1/2	1.9370	0.7480	1/2	UC 209-26		2.27
	UCPA 209-28												UC 209-28		2.19
50 1-7/8	UCPA 210	57.2	130	94	60	14	116	25	M 16	51.6	19.0	M 16	UC 210	PA 210	2.53
	UCPA 210-30	2-1/4	5-1/8	3-45/64	2-23/64	35/64	4-9/16	63/64	5/8	2.0315	0.7480	5/8	UC 210-30		2.60
55 2	UCPA 211	63.5	140	104	66	14	125	25	M 16	55.6	22.2	M 16	UC 211	PA 211	3.17
	UCPA 211-32	2-1/2	5-3/64	4-3/32	2-19/32	35/64	4-59/64	63/64	5/8	2.1890	0.8740	5/8	UC 211-32		3.32
60 2-1/4	UCPA 212	69.9	150	114	68	15	138	25	M 16	65.1	25.4	M 16	UC 212	PA 212	4.17
	UCPA 212-36	2-3/4	5-29/32	4-31/64	2-43/64	19/32	5-7/16	63/64	5/8	2.5630	1.0000	5/8	UC 212-36		4.31
65 2-1/2	UCPA 213	76.2	160	124	70	15	150	25	M 16	65.1	25.4	M 16	UC 213	PA 213	4.96
	UCPA 213-40	3	6-19/64	4-7/8	2-3/4	19/32	5-29/32	63/64	5/8	2.5630	1.0000	5/8	UC 213-40		5.04

Remark: 1) Regular production in "J" tolerance.
 2) Bearing unit with grease holes and grease groove.
 3) Bearing unit without stop pin.