



Shaft dia. mm inch	Unit number	Nominal dimensions										Bolt size mm inch	Bearing number	Housing number	Mass of unit Kg
		mm inch													
		<i>a</i>	<i>e</i>	<i>i</i>	<i>g</i>	<i>t</i>	<i>b</i>	<i>s</i>	<i>z</i>	<i>Bi</i>	<i>n</i>				
25 1	UCFL 305	150	113	16	13	29	80	19	39	38	15	M 16	UC 305	FL 305	0.88
	UCFL 305-16	5-29/32	4-29/64	5/8	3/64	1-9/64	3-5/32	3/4	1-17/32	1.4961	0.5906	5/8	UC 305-16		0.87
30 1-1/8 1-1/4	UCFL 306	180	134	18	15	32	90	23	44	43	17	M 20	UC 306	FL 306	1.34
	UCFL 306-18	7-3/32	5-9/32	45/64	19/32	1-17/64	3-35/64	29/32	1-47/64	1.6929	0.6693	3/4	UC 306-18		1.36
	UCFL 306-20												UC 306-20		1.32
35 1-1/4 1-3/8	UCFL 307	185	141	20	16	36	100	23	49	48	19	M 20	UC 307	FL 307	1.59
	UCFL 307-20	7-9/32	5-35/64	25/32	5/8	1-27/64	3-15/16	29/32	1-59/64	1.8898	0.7480	3/4	UC 307-20		1.65
	UCFL 307-22												UC 307-22		1.61
40 1-1/2	UCFL 308	200	158	23	17	40	112	23	56	52	19	M 20	UC 308	FL 308	2.11
	UCFL 308-24	7-7/8	6-7/32	29/32	43/64	1-37/64	4-13/32	29/32	2-13/64	2.0472	0.7480	3/4	UC 308-24		2.15
45 1-5/8 1-3/4	UCFL 309	230	177	25	18	44	125	25	60	57	22	M 22	UC 309	FL 309	3.07
	UCFL 309-26	9-1/16	6-31/32	63/64	45/64	1-47/64	4-59/64	63/64	2-23/64	2.2441	0.8661	7/8	UC 309-26		3.15
	UCFL 309-28												UC 309-28		3.09
50 1-7/8	UCFL 310	240	187	28	19	48	140	25	67	61	22	M 22	UC 310	FL 310	3.83
	UCFL 310-30	9-29/64	7-23/64	1-7/64	3/4	1-57/64	5-3/64	63/64	2-41/64	2.4016	0.8661	7/8	UC 310-30		3.92
55 2	UCFL 311	250	198	30	20	52	150	25	71	66	25	M 22	UC 311	FL 311	4.66
	UCFL 311-32	9-27/32	7-51/64	1-3/16	25/32	2-1/16	5-29/32	63/64	2-51/64	2.5984	0.9843	7/8	UC 311-32		4.84
60 2-1/4	UCFL 312	270	212	33	22	56	160	31	78	71	26	M 27	UC 312	FL 312	5.59
	UCFL 312-36	10-5/8	8-11/32	1-19/64	55/64	2-13/64	6-19/64	1-7/32	3-5/64	2.7953	1.0236	1	UC 312-36		5.64
65 2-1/2	UCFL 313	295	240	33	25	58	175	31	78	75	30	M 27	UC 313	FL 313	6.99
	UCFL 313-40	11-39/64	9-29/64	1-19/64	63/64	2-9/32	6-57/64	1-7/32	3-5/64	2.9528	1.1811	1	UC 313-40		7.04
70 2-3/4	UCFL 314	315	250	36	28	61	185	35	81	78	33	M 30	UC 314	FL 314	8.42
	UCFL 314-44	12-13/32	9-27/32	1-27/64	1-7/64	2-13/32	7-9/32	1-3/8	3-3/16	3.0709	1.2992	1-1/8	UC 314-44		8.43
75 3	UCFL 315	320	260	39	30	66	195	35	89	82	32	M 30	UC 315	FL 315	9.80
	UCFL 315-48	12-19/32	10-15/64	1-17/32	1-3/16	2-19/32	7-43/64	1-3/8	3-1/2	3.2283	1.2598	1-1/8	UC 315-48		9.71
80 3-1/8	UCFL 316	355	285	38	32	68	210	38	90	86	34	M 33	UC 316	FL 316	13.00
	UCFL 316-50	13-31/64	11-7/64	1-1/2	1-17/64	2-43/64	8-17/64	1-1/2	3-35/64	3.3858	1.3386	1-1/4	UC 316-50		13.03

Remark: 1) Regular production in "J" tolerance.
 2) Bearing unit with grease holes and grease groove.
 3) Bearing unit without stop pin.