



Shaft dia. mm	Unit number	Nominal dimensions mm														Bearing number	Housing number	Mass of unit Kg
		<i>o</i>	<i>g</i>	<i>p</i>	<i>q</i>	<i>s</i>	<i>b</i>	<i>k</i>	<i>e</i>	<i>a</i>	<i>w</i>	<i>j</i>	<i>t</i>	<i>h</i>	<i>Bi</i>			
20	UKT 205	16	12	51	32	19	51	12	76	89	97	32	24	62	35	UK 205	T 205	0.77
25	UKT 206	16	12	56	37	22	57	12	89	102	113	37	28	70	38	UK 206	T 206	1.19
30	UKT 207	16	15	64	37	22	64	12	89	102	129	37	30	78	43	UK 207	T 207	1.48
35	UKT 208	19	18	83	49	29	83	16	102	114	144	49	33	88	46	UK 208	T 208	2.15
40	UKT 209	19	18	83	49	29	83	16	102	117	144	49	35	87	50	UK 209	T 209	2.13
45	UKT 210	19	18	83	49	29	86	16	102	117	149	49	37	90	55	UK 210	T 210	2.29
50	UKT 211	25	21	102	64	35	95	22	130	146	171	64	38	106	59	UK 211	T 211	3.44
55	UKT 212	32	21	102	64	35	102	22	130	146	194	64	42	119	62	UK 212	T 212	4.29
60	UKT 213	32	23	111	70	41	121	26	151	167	224	70	44	137	65	UK 213	T 213	6.16

- Remark: 1) Regular production in "J" tolerance.
 2) Bearing unit with grease holes and grease groove.
 3) Bearing unit without stop pin.